Indoor DV-LED Freestanding Totems P2.5



Maximize visibility, flexibility, and engagement with our all-in-one DV-LED totem solution

Freestanding DV-LED Totem



Effortless Installation & Maintenance

Installing these freestanding displays is a lot simpler than wall mounted counterparts. No matter what your level of experience with DV-LED solutions, installing and maintaining these displays couldn't be easier saving time and money.



Small Footprint Totems

With a depth of 297mm our totem units don't take up valuable floorspace. This opens up more possibilities of where the totems can be placed. Even better the ultra slim DV-LED cabinets make the perceived depth of the units even smaller.



```
297mm
Depth
```

Protective Rear Enclosure

Our DV-LED freestanding totems look great from any angle for a full 360° experience. The rear of the totems has a glossy black finish and are neat in design, hiding any messy cables and fixtures inside the discrete internal locker.

> Discrete Internal Locker



Update Content Remotely

Publish and monitor content from anywhere in the world via the internet using our own cloud-based CMS software, which is designed to be cost-effective and user-friendly. Plus, avoid the hassle associated with coordinating multiple suppliers by sourcing hardware and software from one place.



Ultra-Quiet Operation

These DV-LED totems do not require cooling fans due to their super low heat emissions. Not only does this allow them to run silently, which is especially important in indoor spaces, it also makes them more robust and reliable as there are no moving parts.



Easy Manoeuvrability

Thanks to the integrated swivel castors, these displays offer a portable solution that can be moved around. This is particularly useful for businesses that may want to change the layout of their space frequently or for events and promotions that require temporary placement.



Captivating Image Quality


Integrated Castors

By utilising state-of-the-art SMD technology and advanced video processing, these displays really bring content to life by delivering crystal clarity and lifelike colours without any distortion. This is coupled with rapid refresh rates to ensure seamless content playback.




High Brightness Version Available

For our Freestanding DV-LED Totems we can offer two brightness options. One is a standard 800cd/m² that is perfect for commercial indoor spaces. We also offer a 2,200cd/m² variation that is optimised more for window displays



Key Features



Specification Table

	Columns	1x	2x	3x	4x	5x	6x	7x
	Display Size	80"	91"	107"	126"	147"	169"	192"
LED Display	Display Area (WxHmm)	640x1920	1280x1920	1920x1920	2560x1920	3200x1920	3840x1920	4480x1920
	Resolution (px)	256x768	512x768	768x768	1024x768	1280x768	1536x768	1792x768
	Aspect Ratio	1:3	2:3	1:1	4:3	5:3	2:1	7:3
	Pixel Pitch (mm)	P2.5						
	LED Type	SMD2121						
	Pixel configuration	1R1G1B						
	Brightness (Calibrated)	800cd/m²(2,200cd/m² High Brightness Version Available)						
	Refresh rate	3840Hz						
	Contrast Ratio	6,500:1						
	Viewing Angle - Horizontal	170°						
	Viewing Angle - Vertical	170°						
	Processing	12 bit						
	Frame rate	60 fps						
	Maintenance	Front Service						
Mechnical	Unit Size (mm) (WxHxD)	640x2010x300	1280x2010x300	1920x2010x300	2560x2010x300	3200x2010x300	3840x2010x300	4480x2010x30
	Net Weight (kg)	83.3	166.6	249.9	333.2	416.5	499.8	583.1
Power	Input Voltage	AC220/110 ± 10%, 47~63Hz						
	Average Power Consumption (W)	144	276	408	540	672	804	936
Environmental	IP Rating	IP40						
	Operating Temperature	-10°C to +60°C						
	Operating Humidity	10% to 80%						
	Lifetime	100,000 hours						
Computer	Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)						
	Media Resolution	1920x1080/1080x1920						
	Internal Memory	32GB						
	CPU	Quad-Core Cortex-A17@1.61GHz						
	GPU	Mali-T760 MP4 @600MHz						
	RAM	4GB DDR3						
	USB	USB2.0 HOST (x4)						
	LAN	10/100Mb/s Ethernet						
	Wi-Fi	802.11b/g/n						
	OS	Android 7.1						
	Graphic Engine	OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1						
Package	Included	Totem Frame, DV-LED Cabinets, DV-LED Controller, PPCNET-D Media Player						
	Optional	ТВС						
Warranty	Warranty Period	3 Year Warranty						
	Technical Support				Lifetime			

Why Choose Our Commercial Display Solutions?

